

Short test report No. VFH-12-010-KP**1 Test item**

Initial type testing: Pellet-roomheater Vivo 80 Pellet

2 Client

MCZ Group S.p.A.

Via la Croce, 8

I – 33074 Vigonovo di Fontanafredda (PN)

3 Size and placing of the order

The size of the order includes the testing of the pellet-roomheater Vivo 80 Pellet according to EN 14785 „Residential space heating appliances fired by wood pellets – requirements and test methods“ having regard to the agreements according to clause 15a B-VG „Inverkehrbringen von Kleinfieberungen und die Überprüfung von Feuerungsanlagen und Blockheizkraftwerken“ as well as to the “Erste Verordnung zur Durchführung des Bundes-Immissionsschutzgesetzes (1.BImSchV) - Stufe 2“.

The testing of the pellet-roomheater Vivo 80 Pellet was carried out in the testing rooms of the “Versuchs- und Forschungsanstalt der Hafner Österreichs” (Research and Testing Center of the Austrian stove-fitters). At the testing two tests at nominal heat output, a test at lower heat output as well as a test of the fire safety were carried out with the test-fuel wood pellets.

The placing of the order occurred in September 2011.

4 Results

	No.	Heat output level	Test results			Limit values					
			mg/MJ	% (13% O ₂)	mg/m ³ _N (13% O ₂)	Art. 15a	EN 14785	BImSchV Stufe 2			
CO	1	Nominal	69	0,01	112	500	500	250			
	2	Nominal	52	0,01	85						
	3	Lower	263	-	428						
NO ₂	1	Nominal	82	-	133	150/100 ¹	-	-			
	2	Nominal	81	-	133						
	3	Lower	49	-	80						
OGC	1	Nominal	2	-	2	30	-	-			
	2	Nominal	< 2	-	< 2						
	3	Lower	8	-	11						
Dust	1	Nominal	10	-	20	50/25 ¹	-	30			
	2	Nominal	10	-	19						
	3	Lower	-	-	-						
η (%)	1	Nominal	91,9			78/80 ¹	75	85			
	2	Nominal	92,5								
	3	Lower	95,8								

¹ Limit values valid from 2015.

The requirements of EN 14785 are fulfilled as per clause 9.2 of the test report VFH-12-010-P. The limit values for emissions and efficiency of the agreement according to clause 15a B-VG „Inverkehrbringen von Kleinfieberungen und die Überprüfung von Feuerungsanlagen und Blockheizkraftwerken“ and the “Erste Verordnung zur Durchführung des Bundes-Immissionsschutzgesetzes (1.BImSchV) - Stufe 2“ for automatically loaded small firing plants are fulfilled. The specified nominal heat output (10.5 kW) is achieved.

This short test report is an abstract of the test report VFH-12-010-P. It is only valid in connection with the test report VFH-12-010-P.


Dipl.-Ing. Dr. Thomas Schiffert
Authorized signatory



GZ.: BMWFJ-92.714/0069-I/12/2009

Vienna, 04.06.2012

NB 1733

