

# FLOS 6



AIR - Pellet stoves

FreePoint

Certificate model name : FLOS 6 T1



Nominal power	kW	6
Reduced power	kW	2.8
Introduced thermal power (max)	kW	6.7
Nominal water useful power	kW	-
Reduced water useful power	kW	-
Seasonal energy efficiency	ηs [%]	86
Nominal efficiency	%	90
Reduced efficiency	%	91
Heating volume (min-max)	m³	78 - 168
Nominal CO at 13% O <sub>2</sub>	%	0.008
Reduced CO at 13% O <sub>2</sub>	%	0.012
Emissions CO (13% O <sub>2</sub> ) (min-max)	mg/Nm³	150 - 100
Emissions OGC (13% O <sub>2</sub> ) (min-max)	mg/Nm³	1 - 1
Emissions NOX (13% O <sub>2</sub> ) (min-max)	mg/Nm³	115 - 120
Dust content at 13% O <sub>2</sub> (min- max)	mg/Nm³	19 - 15
Boiler capacity (H <sub>2</sub> O)	l	-
Hopper capacity	kg	10
Combustible		Pellet ø6
Hourly consumption (min-max)	kg/h	0.7 - 1.4
Autonomy (min-max)	h	14 - 7
Ignition electrical absorption (max)	W	370
Operating electrical absorption (max)	W	86
Supply and frequency	V - Hz	230 - 50
Chimney flue depression	Pa	11
Mass of smoke (min-max)	g/sec	2.9 - 4.3
Exhaust fumes temperature (max)	°C	155
Net weight	kg	119
Gross weight	kg	129
Exhaust fumes (A)	Ø mm	80
Hole combustion air inlet (B)	Ø mm	130
Ducting outlet (C)	Ø mm	-
Ducting capability up to	m	-



## MATCH

7023001




Black steel

EAN 8053859018834

## PLUS

- AIRTIGHT sealed chamber
- Integrated WI-FI
- Easy start
- Silent function
- Connection to the room thermostat
- Cast iron inner
- Ceramic glow plug
- Front ventilation
- Integrated temperature sensor
- Daily weekly programming
- Upper exhaust Bi-Flux


## STOVE PACKING



L (cm)	H (cm)	P (cm)
79	93.9	70


VOLUME (m³)
0,52

## LINING PACKING



L (cm)	H (cm)	P (cm)

## STOCKING



## TRANSPORT

